


ACQUATOP PRIMER


Technical Sheet - Ed. 06/2021



COMPANY
WITH QUALITY
MANAGEMENT
SYSTEM
CERTIFIED



INDOOR



OUTDOOR



WATER
BASED



BRUSH



ROLLER



READY
TO USE

One-pack pigmented base coat

DESCRIPTION

Ready-to-use one-pack, pigmented acrylic resin-based base coat dispersed in water with quartz powder additives. Offers outstanding adhesion power. Ideal as primer to enhance adhesion on ceramics, bitumen sheaths, marble, stone and similar products. Particularly suitable for the Acquatop line. For indoor and outdoor use. For professional use.

MAIN PROPERTIES

- Special for difficult substrates

TECHNICAL DATA

Classification UNI 8681	One-pack, physical drying, matt, acrylic primer for base coat with other modifiers, dispersed in water (A.2.C.O.A.2.FD)
Film appearance EN 13300	Matt (≤ 10 gloss 85°)
Thickness EN 13300	Class B, medium ($100 > 300 \mu\text{m}$)
Specific weight	$1200 \pm 50 \text{ g/l}$
pH	7-8
Type of binder	Acrylic
Solid content	$50 \pm 2 \%$
Drying time	Can be overpainted after 6 hrs, completely dry after 12 hrs
VOC	Cat A/h: limit 30 g/l (2010) This product contains a maximum of 2 g/l of VOCs

ACQUATOP PRIMER

Technical Sheet - Ed. 06/2021



COMPANY
WITH QUALITY
MANAGEMENT
SYSTEM
CERTIFIED



CHARACTERISTICS

Colour range	White
Coverage	Coverage with 1 coat: 7-8 m ² /l
Coverage per pack	(15 l): 120 m ² , approx. Coverage varies according to substrate absorption.
Dilution	ready to use, if necessary maximum 10% = 100 ml can be added per litre of product
Diluted with	Water
Overpaintable	Compatibility with other products: compatible with all water-based products

APPLICATION

Suitable Substrates:

Ceramics, bitumen sheaths, marble, stone and similar products

Preparation of the Substrates:

Thoroughly clean the substrates of all oil, grease, and any form of dirt and loose parts.

Use Acquatop Fix as primer on new cement screeds and deteriorated screeds after repair.

Application Procedure:

Dilute ACQUATOP PRIMER as indicated and mix with a low speed mixer. Apply one coat and cross the direction of brush strokes during application.

Type of Equipment:

roller, brush

Ambient Conditions:

min +5°C max +35°C max RH 80%

STORAGE

Packaging:

15 l – 5 l

Duration and conservation:

1 year when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

TECHNOLOGIES/CERTIFICATIONS