

DILUENTE SINTETICO

Technical Sheet - Ed. 01/2023



COMPANY
WITH QUALITY
MANAGEMENT
SYSTEM
CERTIFIED



Synthetic thinner

DESCRIPTION

Synthetic thinner to dilute synthetic and oleosynthetic enamels

MAIN PROPERTIES

TECHNICAL DATA

Specific weight	800 ± 50 g/l
Type of binder	Synthetic thinner
VOC	Not covered by Directive 2004/42/CE

CHARACTERISTICS

Colour range	Clear
Dilution	Ready to use

APPLICATION

Application Procedure:

Suitable for diluting products such as: Aderlac HQ, Waxed matt, Fondo per Legno, Marineria, Marineria Opaco, Micafer, Minio Oleo Fenolico, smooth Muralpac, Rusty. Follow the quantities indicated in the technical data sheet of the finished product.

STORAGE

Storage:

1 year in unopened packages between 5 and 30°C, fear direct exposure to the sun

Disposal and safety indications:

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

Packaging:

0.5l - 1l - 5l - 25l

IVAS Industria Vernici S.p.A. - Via Bellaria, 40 - 47030 San Mauro Pascoli (FC) - Italy
Tel. +39 0541 815811 - Fax +39 0541 815815 - www.gruppoivas.com - ivas@gruppoivas.com

This Technical Sheet is compiled to the best of our technical/scientific knowledge. Nevertheless, it is not binding and does not imply that we are responsible, as the conditions of use are outside our control. It is recommended that the product is always checked as being suitable for the specific application.