



Matt textured washable water-based paint

DESCRIPTION

Washable, texturised water-based fillers made of vinylic resins in aqueous dispersion with special mineral fillers that normalize the surface, concealing small imperfections of the support and giving the surfaces an exceptional opacity. The product has obtained the Ecolabel and Indoor Air Comfort Gold certification; a sign of attention to the quality of a healthy indoor environment. For indoor use.

MAIN PROPERTIES

- Washable
- Filler - uniforming
- Very Matte
- Ecolabel and IACG certificate



TECHNICAL DATA

Volatile organic compounds (VOC)	Cat A/a (2004/42/CE); EU limit 30 g/l (2010). This product contains max 0,10 g/l of VOCs.
Film aspect EN 13300	Very Matt (≤ 5 gloss 85°)
Thickness EN 13300	Class A, fine ($< 100 \mu\text{m}$)
Classification (UNI 8681 / UNI 8682)	One-pack, physical drying matt vinylversatica topcoat paint dispersed in water (B4.C0.A.2.HF)
Wet abrasion resistance (EN 13300 / EN 1062)	Class 2
Specific weight	1520 \pm 50 g/l
	8.3-9
Type of binder	Vinyl poured
Solid content	58 \pm 2%
Drying time	Can be overpainted after 6 hrs, completely dry after 12 hrs
Dirt grip (UNI 10792)	Very low

CHARACTERISTICS

Coverage	14 m ² /l (Kubelka-Munk EN ISO 6504-1 : 06-2019)
Coverage per pack	(14 l): 196 m ² , approx. Coverage varies according to substrate absorption.
Overpaintable	Compatibility with other products: compatible with all water-based products
Colour range	You Color tintometric system can be used for white and colors
Dilution	Water; 10-15% = 100-150 ml per litre of product

APPLICATION

Suitable Substrates:

Cement-based plaster, painted plaster, lime-based plaster and paint, exposed reinforced concrete, precast concrete features and panels, gypsum and fibre cement walls and features.

Ambient Conditions:

min +5°C max +35°C max RH 80%

Preparation of the Substrate:

All substrates must be free of release agents, dry, clean and cohesive. The plasters must be sufficiently seasoned according to the type of material and the manufacturer's instructions. On surfaces with mold or algae, first apply a coat of Sana Solux and wait at least 24 hours before proceeding.

Lime & Gypsum

Filling of all irregularities such as holes, cracks by applying IVASTUCCO fine synthetic resin -based stucco and subsequent sanding with sandpaper.

Consolidation by applying a coat of MICRALICA ultrafine fixative.

Drywall

Filling of all irregularities such as holes, cracks by applying IVASTUCCO fine synthetic resin -based stucco and subsequent sanding with sandpaper.

Consolidation by applying one of MICRALICA ultrafine fixative.

Plaster

Filling of all irregularities such as holes, cracks by applying IVASTUCCO fine synthetic resin -based stucco and subsequent sanding with sandpaper (indoors only).

Depending on the type of plaster, carry out any repairs or leveling with UNIFORM BIANCO/GRIGIO.

Consolidation by applying a coat of MICRALICA ultrafine fixative.

N.B. In case of uneven surfaces (patched up, partially coloured, grouted, etc.) or application of dark and intense colours, it is advisable to apply a uniform base coat from the primer range, PRIME TECH, RASOFONDO 0.1-0.3 (IVAS) depending on the desired particle size

Type of Equipment:

brush, roller

Application Procedure:

Dilute ECOTEX as indicated and mix with a low speed mixer. Apply two coats, waiting at least 6 hours between coats. For brush or roller painting, to achieve a uniform appearance, cross the direction of strokes during application.

STORAGE

Disposal and safety indications:

Safety data sheet available on request.

Attention! In case of vaporization, dangerous respirable droplets may form. Do not breathe vapors or mists. Contains: Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one and 2-methyl-2H-isothiazolin-3-one (3:1), 1,2-Benzisothiazol-3(2H)-one May cause an allergic reaction. If you consult a doctor, have the product container or label available. Keep out of reach of children. Dispose of the product/container according to current regulations.

Do not throw unused product residues into the sewer system. Do not dispose of in the toilet, sink or waste bin. Take the empty container and any unused product to waste collection centers. (Contact your local environmental services company.)

Avoid wasting paint by estimating how much paint you will need. Store unused paint for future use. Reusing paint is an effective way of reducing the environmental impact of products throughout their entire life cycle. Remove excess product from utensils before washing them. Clean utensils with water. Close the can after use. Store only in a closed container, in a well-ventilated place, protected from frost, heat and humidity.

Packaging:

14 l - 5 l - 2.5 l - 1 l Quart, Gallon, 5 Gallons

Storage:

1 year when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

TECHNOLOGIES/CERTIFICATIONS

