



Elastic filler skimming plaster

DESCRIPTION

Elastomer-based filler in water emulsion, it contains alkal- and light-resistant pigments, natural and synthetic fibres, extenders. Can be used as elastic, waterproofing filler/skim coat to fill cracks or fissures, for outdoor use. Specially formulated for skimming of plasters with cracks and fissures. Can be used with Armatex micro. For outdoor use. For professional use.

MAIN PROPERTIES

- Eliminates cracks
- Excellent for filling cracks

TECHNICAL DATA

Classificazione UNI 8681	One-pack, physical drying, matt acrylic base coat plaster dispersed in water (E2.C.O.A.2.FA)
Film aspect EN 13300	Matt G3 (≤ 10 gloss 85°)
Maximum granulometry EN 1062	S1, Fine ($< 100 \mu\text{m}$)
Maximum applicable thickness	5mm in two coats
Bulk volume in paste	1400 \pm 50 g/l
pH	7-8
Type of binder	Acrylic (UNI 8681: FA)
Solid content	70 \pm 2 %
VOC	Cat A/a: limit 30 g/l (2010) This product contains a maximum of 14 g/l of VOCs

CHARACTERISTICS

Colour range	White
Coverage	1.4 kg/m ² per mm of thickness
Coverage per pack	Ready to use
Dilution	Water
Diluted with	Under normal conditions, it can be covered after 48 hours; however, drying time depends on the absorption of the substrate and environmental conditions
Overpaintable	Compatibility with other products: ELASTUCCO can be overpainted with all products in the Ivasum (IVAS) line and with other water-based products.

APPLICATION

Suitable Substrates:

Cement-based plaster, lime-based plaster, painted plaster, exposed reinforced concrete, precast concrete panels and features and fibre cement

Preparation of the Substrate:

All substrates should be carefully prepared by manual brushing and/or pressure washing, depending on the nature and extent of the dirt on the surface to be treated

New walls:

application by brush of a coat of Primacril (IVAS) fixative diluted 1:1 with water is recommended to eliminate dust and to even out absorption, especially in the case of prefabricated concrete panels

Painted walls:

remove any loose paint and brush on a coat of Nitrofix (IVAS) solvent-based fixative

Application Procedure:

Depending on the desired thickness, using a spatula, apply in several coats waiting 12 hrs between coats

Type of Equipment:

spatula

Ambient Conditions:

min +5°C max +40°C

STORAGE

Packaging:

20 kg – 5 kg

Duration and Preservation:

6 months on a pallet and when stored in a dry place in undamaged packages at between 5° and 30°C.

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

TECHNOLOGIES/CERTIFICATIONS

