

I DILUENTI (Thinners)

PRODUCT	IDENTIFICATION (suitable for)	ABSOLUTE GRAVITY	FLAMMABILITY	LABELLING	PACKAGE
<i>Diluyente Nitro Antinebbia (Nitro Anti-fog Thinner)</i>	<i>Antiruggine per Carrozzeria, Bitumflex, Cloro-Pool, Clorex, Nitrofix, Rapidex</i>	<i>910 ± 20 g/l</i>	<i>≤ 21°C</i>	<i>Fiamma-Xn</i>	<i>0,5 l – 1 l 5 l – 25 l</i>
<i>Diluyente per Epossidici (Epoxy Thinner)</i>	<i>Epozinco, Primer-Pool</i>	<i>820 ± 20 g/l</i>	<i>21°C < Pl ≤ 55</i>	<i>R10</i>	<i>1 l – 5 l – 25 l</i>
<i>Diluyente per Poliuretanic (Polyurethane Thinner)</i>	<i>Antigraffiti, Betonglass, Ivaglass, Paviglass</i>	<i>900 ± 20 g/l</i>	<i>21°C < Pl ≤ 55</i>	<i>R10</i>	<i>1 l – 5 l – 25 l</i>
<i>Diluyente per Spartitraffico (Thinner for Road Marking Product)</i>	<i>Spartitraffico</i>	<i>780 ± 20 g/l</i>	<i>≤ 21°C</i>	<i>Fiamma-Xn</i>	<i>1 l – 5 l – 25 l</i>
<i>Diluyente Sintetico (Synthetic Thinner)</i>	<i>Aderlac, Cerato, Ivafer, Ivaspac, Marineria, Marineria opaco, Micafer, Minio Oleofenolico, Muralpac Liscio</i>	<i>825 ± 20 g/l</i>	<i>21°C < Pl ≤ 55</i>	<i>R10</i>	<i>0,5 l – 1 l 5 l – 25 l</i>

N.B. This Technical Information Sheet is compiled to the best of our technical/scientific knowledge. Nevertheless, it is not binding and does not imply that we are responsible, as the conditions of use are outside our control. It is recommended that the product is always checked as being suitable for the specific application.

IVAS Industria Vernici S.p.A. – Via Bellaria, 40 – 47030 San Mauro Pascoli (FC) – Italy
 Phone +39 0541 815811 – Fax +39 0541 815815
www.gruppoivas.com ivas@gruppoivas.com

Company with quality management system certified UNI EN ISO 9001