



Skimming plaster in paste form

DESCRIPTION

Fine skimming and filling plaster based on synthetic resins dispersed in water and selected fillers. Good flow and spreadability. It does not cause cracks. For indoor use. For professional use.

MAIN PROPERTIES

- Universal filler

TECHNICAL DATA

Classificazione UNI 8681	One-pack, physical drying matt vinyl versatate plaster for base coat dispersed in water (E2.A.O.A.2.HF).
Film aspect EN 13300	Matt G3 (≤ 10 gloss 85°)
Maximum granulometry EN 1062	S1, Fine ($< 100 \mu\text{m}$)
Maximum applicable thickness	5mm in two coats
Bulk volume in paste	$1860 \pm 50 \text{ g/l}$
pH	7-8
Type of binder	vinyl versatate (UNI 8681: HF)
Solid content	$75 \pm 2\%$
VOC	Cat A/a: limit 30 g/l (2010) This product contains a maximum of 10 g/l of VOCs

CHARACTERISTICS

Colour range	White
Coverage	1 kg/m ² per mm of thickness
Coverage per pack	Ready to use
Dilution	Water
Diluted with	Under normal conditions, it can be covered after 2 hours; however, drying time depends on the absorption of the substrate and environmental conditions
Overpaintable	Compatibility with other products: compatible with all water-based products

APPLICATION

Suitable Substrates:

Cement-based plasters, lime-based plasters, painted plasters, base coat for finishing with Rasobell (IVAS)

Preparation of the Substrate:

All substrates should be carefully prepared by manual brushing and/or washing

Application Procedure:

Apply with a spatula in several coats

Type of Equipment:

spatula

Ambient Conditions:

min +5°C max +35°C

STORAGE

Packaging:

25 kg – 5 kg – 1 kg – 0.500 kg

Duration and Preservation:

1 year on a pallet and when stored in a dry place in undamaged packages at between 5 and 30°C.

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

TECHNOLOGIES/CERTIFICATIONS