

M PROTECTION SEALER

Technical Sheet - Ed. 10/2019



Water repellent, stabilising water-based protection, particularly suited for lime-based decorative finishes. For indoor and outdoor use.

DESCRIPTION

Containing modified acrylic resins, it protects absorbent decorative finishes, even those that are difficult to treat, while maintaining the original appearance. For professional use.

PROPERTIES

- Permeable protective varnish
- Reduces absorption by the treated finish

TECHNICAL DATA

Classification UNI 8681	One-pack, physical drying matt acrylic topcoat varnish dispersed in water (A4.B.O.A.O.FA).
Film appearance UNI 13300	Matt (≤ 10 gloss 85°)
Thickness UNI 13300	Class A, fine ($< 100 \mu\text{m}$)
Specific weight	$1030 \pm 50 \text{ g/l}$
pH	8 – 9
Type of binder	Acrylic
Solid content	$23 \pm 2\%$
Drying time	Can be overpainted after 2 hrs, completely dry after 12 hrs
VOC	Cat A/c: limit 40 g/l (2010) This product contains a maximum of 1 g/l of VOCs

M PROTECTION SEALER

Technical Sheet - Ed. 10/2019

CHARACTERISTICS

Colour range	Transparent
Coverage	With the application of 1 coat: 10-12 mq/l (107-129 sq ft/l)
Coverage per pack	(5 l): 50 -60 mq, approx. Coverage varies according to substrate absorption.
Dilution	Ready to use.
Diluted with	Water
Overpaintable	Compatibility with other products: with water-based paints or coatings

APPLICATION

Suitable Substrates:

Plastic coatings, paints, cement-based and lime-based plasters

Preparation of the Substrates:

All substrates should be thoroughly prepared by manual brushing.

Application Procedure:

Mix before use. Using a brush or glove, apply two coats of the product waiting 4 h between coats and using a cloth to remove any excess product.

Type of Equipment:

brush, glove, cloth

Ambient Conditions:

min +5°C max +40°C max RH 80%

STORAGE

Packaging:

5 l – 1 l

Duration and conservation:

1 year when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet.

CERTIFICATION\CLASSIFICATION

