

METRO CERA (Effetto Satin)

METROPOLIS®

MADE IN ITALY

Technical Sheet - Ed. 06/2021



Wax for finishes

DESCRIPTION

Wax for special finishes, suitable for indoor decorations with the effect of satin-finished marble. Can be applied on tempera, washable surfaces, quartz, spatula-applied fillers and lime based products. For indoor use. For professional use.

MAIN PROPERTIES

- Protective treatment
- Satin finish effect



TECHNICAL DATA

Classification UNI 8681	One-pack, physical drying semi-gloss acrylic topcoat paint, dispersed in water (A4.C.O.A.1.FA)
Film appearance EN 13300	Satin (< 10 gloss 85° > 60 gloss 60°)
Thickness EN 13300	Class A, fine (< 100 µm)
Specific weight	960 ± 50 g/l
pH	7-8
Type of binder	Acrylic
Solid content	30 ± 2%
Drying time	Can be overpainted after 4 hrs, completely dry after 12 hrs
VOC	Cat A/l: limit 200 g/l (2010) This product contains a maximum of 23 g/l of VOCs

CHARACTERISTICS	
Colour range	Transparent
Coverage	With the application of 1 coat: 6-8 mq/l (65-86 sq ft/l)
Coverage per pack	(5 l): 40 mq, approx. Coverage varies according to substrate absorption.
Dilution	maximum 15% = 150 ml per litre of product with spatula: ready to use
Diluted with	Water
Overpaintable	Compatibility with other products: all solvent free products. After sanding and applying a coat of Metro Fix, METRO CERA can be overpainted with most good quality indoor paints

APPLICATION

Suitable Substrates:

Lime-based plaster and topcoats, painted plaster, gypsum features and skimmed walls

Preparation of the Substrates:

New plasters

We recommend preparation with one or more coats of Metro Stuc skimming plaster before painting and then finishing with METRO CERA.

Painted plasters

Remove any old, loose paint and smooth out everything with Metro Stuc before applying the paint and treating with METRO CERA.

Application Procedure:

Can be applied by brush or spatula, or can be applied by brush and worked with spatula depending on the desired aesthetic effects

Type of Equipment:

brush (Klimt Brush), steel trowel (Pollock Stainless Steel trowel), glove (Matisse Glove, Miró Glove)

Ambient Conditions:

Min +5°C max +40°C max RH 80%

STORAGE

Packaging:

5 l – 1 l

Duration and conservation:

2 years when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight.

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet.

TECHNOLOGIES/CERTIFICATIONS