



**Water-based fixative with great stabilising properties. For indoor and outdoor use.**

## DESCRIPTION

Water-based acrylic paint containing fine particles with great penetrating properties, particularly suitable for impregnation. For professional use.

## PROPERTIES

- Consolidates substrates
- High coverage

## TECHNICAL DATA

Classification UNI 8681	One-pack, physical drying matt or semi-gloss acrylic paint dispersed in water for topcoat and/or simple surface impregnation (AO/4.C.O.A.1.FA)
Film appearance UNI 13300	Matt ( $\leq 10$ gloss 85°)
Thickness UNI 13300	Class A, fine ( $< 100 \mu\text{m}$ )
Specific weight	$1000 \pm 50 \text{ g/l}$
pH	8 - 9
Type of binder	Acrylic
Solid content	$40 \pm 2\%$
Drying time	On surfaces: 2 hrs completely dry after 12 hrs
VOC	Cat A/h: limit 30 g/l (2010) This product contains a maximum of 20 g/l of VOCs

## CHARACTERISTICS

Colour range	Transparent
Coverage	With the application of 1 coat: 40-50 mq/l (430-538 sq ft/l)
Coverage per pack	(10 l): 500 mq, approx. Coverage varies according to substrate absorption.
Dilution	for impregnation: 400% = 4 litres per litre of product for finishes: from 1 to 3 litres per litre of product, depending on the degree of satin finish desired
Diluted with	Water
Overpaintable	Compatibility with other products: with water-based paints or coatings

## APPLICATION

### Suitable Substrates:

Cement-based plasters, gypsum features and skimmed walls, exposed reinforced concrete, precast concrete features, fibre cement

### Preparation of the Substrates:

All substrates should be carefully prepared by manual brushing and/or washing with a pressure washer, depending on the nature and extent of the dirt on the surface to be treated

### Application Procedure:

If used as a substrate impregnating agent, apply a single coat of the product; if used as wall finish, apply two coats waiting 4 hours between coats.

### Type of Equipment:

Type: brush for impregnation, short-haired wool roller (Magritte Roller), airless spraying equipment if used as topcoat

### Ambient Conditions:

min +5°C max +40°C max RH 80%

## STORAGE

### Packaging:

10 l – 5 l – 1 l

### Duration and conservation:

2 years when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet.

## CERTIFICATION\CLASSIFICATION

