



Rheological liquid thickener

DESCRIPTION

Rheological liquid thickener. Designed to thicken the products in the Metropolis® range (Venezia S, Lady Vi, Hot Metal, Soul Cement, Factor, Metro Blackboard, Metroresin Body, Metroresin Shine lines of products). For professional use. For indoor and outdoor use.

MAIN PROPERTIES

- Thickener

TECHNICAL DATA

Classification UNI 8681	Additive for paints and coatings
Film appearance EN 13300	na
Thickness EN 13300	Class A, fine (< 100 µm)
Specific weight	1000 ± 50 g/l
pH	8-9
Type of binder	n.a.
Solid content	14 ± 2 %
Drying time	It depends on the characteristics of the product used
VOC	Not covered by Directive 2004/42/CE

CHARACTERISTICS

Colour range	
Coverage	As needed
Coverage per pack	As needed
Dilution	Ready to use
Diluted with	Water
Overpaintable	See the data sheet for the product it has been added to

APPLICATION

Suitable Substrates:

The product cannot be used alone but always as an additive

Preparation of the Substrates:

See the data sheet for the product it has been added to

Application Procedure:

When stirring the Metropolis product to be thickened using a mixing drill, add METRO THICK in a stream until the desired product consistency for application is obtained.

Type of Equipment:

Mixing drill

Ambient Conditions:

See the data sheet for the product it has been added to

STORAGE

Packaging:

0.25 l

Duration and conservation:

2 years when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight.

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet.

TECHNOLOGIES/CERTIFICATIONS