



## Lime putty-based marble stucco

### DESCRIPTION

Very fine-grained eco-friendly stucco for interior decorations to obtain encaustic-type glossy marbled finishes. Workable alone or in combination with OLD TIME MAX. The TVOC Class A+ certificate makes it suitable for compliance with CAM, Leed Breeam protocols. For indoors and outdoors. For professional users only.

### MAIN PROPERTIES

- Eco-friendly
- Mineral
- Glossy marble effect
- Outstanding workability



### TECHNICAL DATA

Water absorption (class W) (EN 1062)	Class W1, High
Film aspect EN 13300	Depending on the processing
Classification (UNI 8681 / UNI 8682)	Thick-coat paint for the topcoat in a one-pack, chemical-physical drying, matt finish, dispersed in water (C.4.C.O.D.2.C.SA)
Solid content	60 ± 2%
Granulometry (EN 13300 / EN 1062)	200µ max
Vapour permeability (class V) (EN 1062)	Sd 0.06 ± 0.02 m; Class V1 High
Specific weight	1560 ± 50 g/l
Drying time	48 hrs to 20°C
Type of binder	Lime
	> 12 ± 0.2
Volatile organic compounds (VOC)	For interior use: Cat A/a; limit 30 g/l (2010). This product contains a maximum of 1,00 g/l of VOCs. For outdoor use: Cat A/c; limit 40 g/l (2010). This product contains a maximum of 1,00 g/l of VOCs.

### CHARACTERISTICS

Overpaintable	Compatibility with other products: water-based products
Dilution	Water; Ready to use
Colour range	Materia Naturale colour chart. Use of special colours that require organic pigments to achieve the tone are not recommended
Coverage	0.8 - 1 m <sup>2</sup> /kg with 2 coats application
Coverage per pack	(20 kg): 20 mq, approx. (2 coats) Coverage varies according to the roughness of the substrate.

### APPLICATION

#### Ambient Conditions:

Min +5°C max +40°C max RH 80%

#### Type of Equipment:

steel trowel (Pollock Stainless Steel trowel)

#### Suitable Substrates:

Concrete, civil plasters, painted civil plasters, plaster skim coats and plasterboards, surfaces already prepared and treated with Old Times Max, mineral substrates

## Application Procedure:

With the wall completely dry, after applying the primer or fixative, mix the product until obtaining a homogeneous paste without lumps, apply a first homogeneous coat of OLD TIME FINISH with a stainless steel trowel and wait for it to dry completely. With the first coat completely dry (12 hours), apply the second coat, spreading the product evenly over the entire surface, creating a flat surface without depressions, but not shiny. Once the second coat is completely dry (12 hours), apply the third coat with short spatula strokes with a width of about 1 m<sup>2</sup> at a time, then smooth with a 45° inclined trowel. The shine is obtained by pressing the steel trowel with the right angle on the surface just applied.

## Notes:

Any presence of water on the surface is to be considered normal and must be removed before use. Consistency. For each specific area, we recommend using product from the same batch, otherwise there may be slight differences in shade.

## Preparation of the Substrate:

All substrates must be sufficiently seasoned, carefully prepared by manual brushing and/or washing with a pressure washer depending on the nature of the dirt deposited on the surfaces to be treated. Old loose or flaking paint must be removed. On surfaces with the presence of algae or mold, treat with the VITASANA SOLUX sanitizing cycle. In the presence of grouted or dusty parts, apply a coat of Metro Fix or for mineral substrates, IVASIL PRIMER S or SILOFIX inorganic fixative

Plasterboard, plaster smoothing,

Application of a coat of Metro fix acrylic fixative, wait for drying and complete with the application of a coat of DESIGN COVER (METROPOLIS) opaque primer.

CLS and new civil plasters

Application of a coat of matt base coat DESIGN COVER (METROPOLIS).

Already painted plaster

Depending on the type of plaster, carry out any restorations or smoothings with UNIFORM BIANCO/GRIGIO, in the case of mineral plasters, use ASFODELO/ARTEMISIA

Application of a coat of Metro fix acrylic fixative or IVASIL PRIMER SILOFIX inorganic fixative for mineral substrates

Application of a coat of matt base coat DESIGN COVER (METROPOLIS).

## STORAGE

### Packaging:

20 Kg - 5 Kg - 1 Kg

### Storage:

2 years when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight.

### Disposal and safety indications:

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet.

## TECHNOLOGIES/CERTIFICATIO

