

# OLD TIME MAX SP

Technical Sheet - Ed. 10/2019



**Plaster paste containing lime putty and marble particles. Ideal for historic-artistic building finishes and to achieve special finishes. For indoor and outdoor use.**

## DESCRIPTION

Natural colour plaster paste containing lime putty, marble particles and non-polluting additives. Ideal for historic-artistic building finishes and to achieve special finishes. For professional use.

## PROPERTIES

- Breathable
- Predominantly mineral composition

## TECHNICAL DATA

Classificazione UNI 8681	Thick-coat paint for the topcoat in a one-pack, chemical-physical drying, matt finish, dispersed in water (C.4.C.O.D.2.C.SA)
Film aspect UNI 13300	Matt ( $\leq 10$ gloss $85^\circ$ )
Maximum granulometry UNI 1062	1000 $\mu\text{m}$ , S3, Thick ( $< 1500 \mu\text{m}$ )
Specific weight	1700 $\pm 50$ g/l
pH	$> 11$
Type of binder	Lime
Solid content	72 $\pm 2\%$
Vapour permeability UNI 1062	Sd 0.0281 $\pm 0.02$ m; Class V1 High $\mu=28$
Water absorption UNI 1062	Class W1, High
Drying time	Can be overpainted after 6 hrs, completely dry after 24 hrs
VOC	Cat A/a: limit 30 g/l (2010) This product contains a maximum of 29 g/l of VOCs

## CHARACTERISTICS

Colour range	Materia Naturale colour chart. Use of special colours that require organic pigments to achieve the tone are not recommended
Coverage	With the application of 2 coat: 0.4 mq/Kg (4,3 sq ft/Kg)
Coverage per pack	(25 Kg): 10 mq, approx. Coverage varies according to the roughness of the substrate.
Dilution	Ready to use; add a little water if necessary to achieve the right consistency
Diluted with	Water
Overpaintable	Compatibility with other products: water-based products

## APPLICATION

### Suitable Substrates:

Cement-based plaster, painted plaster, lime-based plaster and paint.

### Preparation of the Substrate:

New surfaces:

no preparation required. Make sure that fresh plaster has set before applying.

Old surfaces:

All substrates should be carefully prepared by manual brushing and/or washing with a pressure washer, depending on the nature and extent of the dirt on the surface to be treated. Old organic paint should be removed.

### Application Procedure:

Thoroughly wet the substrate. Mix until a smooth, lump-free mixture is obtained. Apply two or more coats of OLD TIME MAX SP with a stainless steel trowel, waiting for one coat to dry completely before applying the next. Finish the surface thus obtained with a sponge or wood trowel

### Type of Equipment:

stainless steel, sponge or plastic trowel (for rustic finishes).

### Ambient Conditions:

min +5°C max +40°C max RH 80%

## STORAGE

### Packaging:

25 Kg

### Duration and Preservation:

2 years when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

## CERTIFICATION\CLASSIFICATION

