



Breathable, lime putty-based paint for mineral finishes in buildings of special artistic interest. Long-lasting attractive effect, easy to apply. For indoor and outdoor use.

DESCRIPTION

Lime putty-based, contains natural colours and stabilizing additives modified with resin dispersion. Suitable for application on both old and new mineral plasters, for mineral finishes in buildings of particular artistic interest. For professional use.

PROPERTIES

- Breathable
- Predominantly mineral composition

TECHNICAL DATA

Classificazione UNI 8681	One-pack, chemical-physical drying matt vinylic topcoat paint dispersed in water (B4.C.O.AC.2.C.SA)
Film aspect UNI 13300	Matt (≤ 10 gloss 85°)
Maximum granulometry UNI 1062	S1, Fine ($< 100 \mu\text{m}$)
Specific weight	1500 \pm 50 g/l
pH	> 11
Type of binder	Lime
Solid content	60 \pm 2%
Vapour permeability UNI 1062	Sd 0.004 \pm 0.02 m; Class V1 High $\mu=40$
Water absorption UNI 1062	Class W1, High
Drying time	Can be overpainted after 6 hrs, completely dry after 24 hrs
VOC	Cat A/a: limit 30 g/l (2010) This product contains a maximum of 30 g/l of VOCs

CHARACTERISTICS

Colour range	Materia Naturale colour chart. Use of special colours that require organic pigments to achieve the tone are not recommended
Coverage	With the application of 2 coat: 3 mq/l (32 sq ft/l)
Coverage per pack	(14 l): 42 mq, approx. Coverage varies according to the roughness of the substrate.
Dilution	20-30% = 200-300 ml per litre of product
Diluted with	Water
Overpaintable	Compatibility with other products: compatible with all water-based products

APPLICATION

Suitable Substrates:

Mineral plasters (old and new).

Preparation of the Substrate:

Masonry substrates:

The substrates must be carefully prepared by manual brushing and/or by washing and/or pressure washer, depending on the nature and extent of the dirt on the surface to be treated. Poorly adhering coats of old paint must be removed, then apply a coat of Metro Fix. Make sure that fresh plaster has set before applying.

Application Procedure:

Mix the product before use; first apply a coat of Metrofix fixative. Apply the first coat of OLD TIME using a brush. Apply subsequent coats waiting 12-24 hrs between coats

Type of Equipment:

short-haired wool roller (Magritte Roller)

Ambient Conditions:

min +5°C max +40°C max RH 80%

STORAGE

Packaging:

14 l – 5 l – 1 l

Duration and Preservation:

2 years when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

CERTIFICATION\CLASSIFICATION

