


PITTURA PER INTERNI EXTRA

Scheda Tecnica - Ed. 06/2021



Breathable water-based wall paint in soft colours

DESCRIPTION

Water-based paint containing vinyl-versatic resins dispersed in water, specially designed to optimize application with brush and roller and achieve utmost breathability. Pastel colours can be produced. For indoor use. For professional use.

MAIN PROPERTIES

- non-drip



TECHNICAL DATA

Classification UNI 8681	One-pack, physical drying matt vinyl versatate topcoat paint dispersed in water. (B4.C.O.A.2.HF)
Film appearance EN 13300	Matt (≤ 10 gloss 85°)
Thickness EN 13300	Class A, fine ($< 100 \mu\text{m}$)
Hiding power EN 13300	Class 3
Specific weight	$1680 \pm 50 \text{ g/l}$
pH	7-8
Type of binder	Vinyl versatate
Solid content	$71 \pm 2\%$
Vapour permeability EN 1062	Class V1 - High
Drying time	Can be overpainted after 4 hrs, completely dry after 12 hrs
VOC	Cat A/a: limit 30 g/l (2010) This product contains a maximum of 12 g/l of VOCs

PITTURA PER INTERNI EXTRA



Scheda Tecnica - Ed. 06/2021

CHARACTERISTICS	
Colour range	White and Colours IP indoor selection (un soffio di colore)
Coverage	With the application of 2 coats: 3-4 m ² /l
Coverage per pack	(14 l): 56 m ² , approx. Coverage varies according to substrate absorption
Dilution	40% = 400 ml per litre of product
Diluted with	Water
Overpaintable	Compatibility with other products: compatible with all water-based products

APPLICAZIONE

Suitable Substrates:

Cement-based plaster, painted plaster, lime-based plaster and paint, exposed reinforced concrete, precast concrete features and panels, gypsum and fibre cement walls and features.

Preparation of the Substrates:

All substrates must be free of release agents and must be dry, clean and coherent. Plasters must be sufficiently cured according to the type of material and manufacturer's instructions. On surfaces with mould or algae, first apply a coat of Sana Solux and wait at least 24 hours before proceeding. In the case of old paint or dusty substrates, we recommend applying a coat of ACRILICA 100 consolidating primer or removing them if this is not sufficient.

Application Procedure:

Dilute PITTURA PER INTERNI EXTRA as indicated and mix with a low speed mixer. Apply two coats, waiting at least 4 hours between coats. For brush or roller painting, to achieve a uniform appearance, cross the direction of strokes during application.

Type of Equipment:

brush, roller, airless spraying equipment

Ambient Conditions:

min +5°C max +35°C max RH 80%

STORAGE

Packaging:

14 l – 5 l – 2.5 l

Duration and conservation:

1 year when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

TECHNOLOGIES/CERTIFICATIONS