


PRIMACRIL


Technical Sheet - Ed. 06/2021



COMPANY
WITH QUALITY
MANAGEMENT
SYSTEM
CERTIFIED



INDOOR



OUTDOOR



WATER
BASED



BRUSH



ROLLER

High penetrating, water-based fixative

DESCRIPTION

Water-based fixative with utmost penetration and resistance to alkalis, formulated for superb protection on plasters, both indoor and outdoor (including chalky plasters), and to ensure uniform absorption. Particularly suitable for plasterboard substrates. For indoor and outdoor use. For professional use.

MAIN PROPERTIES

- High penetration
- Specific for RC

TECHNICAL DATA

Classification UNI 8681	One-pack, physical drying, acrylic consolidating primer dispersed in water, for simple surface impregnation, matt finish (G.O.C.O.A.2.FA)
Film appearance EN 13300	Matt (≤ 10 gloss 85°)
Thickness EN 13300	Class A, fine ($< 100 \mu\text{m}$)
Specific weight	$1020 \pm 50 \text{ g/l}$
pH	7-8
Type of binder	Acrylic
Solid content	$18 \pm 2\%$
Drying time	Can be overpainted after 6 hrs, completely dry after 12 hrs
VOC	Cat A/h: limit 30 g/l (2010) This product contains a maximum of 1 g/l of VOCs

CHARACTERISTICS

Colour range	Transparent
Coverage	With the application of 1 coat: 10-12 m ² /l
Coverage per pack	(25 l): 300 m ² , approx. Coverage varies according to substrate absorption.
Dilution	50% = 500 ml per litre of product
Diluted with	Water
Overpaintable	Compatibility with other products: compatible with all water-based products

APPLICATION

Suitable Substrates:

Cement-based plaster, lime-based plaster and paint, organic painted plaster, gypsum skimmed walls, mineral substrates, fibre cement, brick, wood, insulation panels

Preparation of the Substrates:

All substrates must be free of release agents and must be dry, clean and coherent. Plasters must be sufficiently cured according to the type of material and manufacturer's instructions. On surfaces with mould or algae, first apply a coat of Sana Solux and wait at least 24 hours before proceeding as indicated in the technical data sheet. In the case of old, peeled and deteriorated paints, removal is recommended.

Application Procedure:

Dilute PRIMACRIL as indicated and mix with a low speed mixer. Apply one coat and cross the direction of brush strokes during application.

N.B.: always check that the treated surface is not glossy, if necessary increase the dilution.

Type of Equipment:

brush, roller

Ambient Conditions:

min +5°C max +35°C max RH 80%

STORAGE

Packaging:

25 l – 5 l – 1 l

Duration and conservation:

1 year when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

TECHNOLOGIES/CERTIFICATIONS