



SANA SOLUX SPRAY

Technical Sheet - Ed. 06/2021




INDOOR



OUTDOOR



WATER
BASED



AIRLESS

Sanitising solution

DESCRIPTION

Water-based sanitisation solution containing specific active ingredients to clean and restore masonry substrates with an intense presence of mould, fungi and algae. For indoor and outdoor use. For professional use.

MAIN PROPERTIES

- Sanitizing solution

TECHNICAL DATA

Classification UNI 8681	Sterilizing solution, colourless, non-film-forming
Film appearance EN 13300	
Thickness EN 13300	Class A, fine (< 100 µm)
Specific weight	1000 ± 50 g/l
pH	7-8
Type of binder	n.a.
Solid content	< 2,5 %
Drying time	Fully dry: 6-8 hrs
VOC	Not covered by Directive 2004/42/CE

SANA SOLUX SPRAY

Technical Sheet - Ed. 06/2021



CHARACTERISTICS

Colour range	Transparent
Coverage	Coverage with 1 coat: 10 m ² /l
Coverage per pack	(0.5 l): 5 m ² , approx. Coverage varies according to substrate absorption.
Dilution	Ready to use
Diluted with	Water
Overpaintable	Compatibility with other products in the "Vita Sana" Ivas line

APPLICATION

Suitable Substrates:

Cement-based plaster, lime-based plaster and paint, painted plaster, plaster skimmed walls and gypsum features, exposed reinforced concrete, precast concrete panels, fibre cement

Preparation of the Substrates:

All substrates must be free of release agents and must be dry, clean and coherent. Plasters must be sufficiently cured according to the type of material and manufacturer's instructions. On surfaces with mould or algae, first apply a coat of Sana Solux and wait at least 24 hours before proceeding.

Application Procedure:

Apply the product on the damaged parts, wait at least 24 hours, brush to remove the inert spores

Type of Equipment:

spraying equipment

Ambient Conditions:

min +5°C max +35°C max RH 80%

STORAGE

Packaging:

0.5 l

Duration and conservation:

6 months when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

TECHNOLOGIES/CERTIFICATIONS

Ivas Industria Vernici S.p.A. – Via Bellaria, 40 – 47030 San Mauro Pascoli (FC) – Italy

Phone: +39 0541 815811 – Fax +39 0541 815815 - www.gruppoivas.com – ivas@gruppoivas.com

This Technical Sheet is compiled to the best of our technical/scientific knowledge. Nevertheless, it is not binding and does not imply that we are responsible, as the conditions of use are outside our control. It is recommended that the product is always checked as being suitable for the specific application.