



TASSELLO H3



UNIVERSAL PERCUSSION ANCHOR WITH SYNTHETIC NAIL AND FLEXIBLE DISK APPROVED FOR USE ON CONCRETE, SOLID BRICK AND HOLLOW CORE BRICK STRUCTURES. ANCHORING DEPTH: 25 MM. CERTIFIED ETA-14/0130 (USAGE CATEGORIES: A B C). THE FLEXIBLE DISK ENSURES SECURING ON THE INSULATION PANEL, EVEN IF THE HOLE IS SLIGHTLY ON A SLANT.

TECHNICAL DATA

Anchor diameter	8 mm
Disk diameter	60 mm
Depth of hole	35 mm
Anchoring depth	25 mm
Categories of use as per ETA	A, B, C
European technical certification	ETA – 14/0130

WEIGHT BEARING CAPACITY CHARACTERISTICS

Normal concrete C12/15 as per EN 206-1	0.6 kN
Normal concrete C16/20-C50/60 as per EN 206-1	0.6 kN
Construction bricks (Mz) as per DIN 105	0.6 kN
Solid chalky sandstone brick (KS) as per DIN EN 106	0.6 kN
Multi-hole hollow bricks (Hz) as per DIN, bulk density, $\geq 1.2 \text{ kg/dm}^3$	0.5 kN
Multi-hole hollow bricks (Hz) as per DIN, bulk density, $\geq 0.9 \text{ kg/dm}^3$	0.5 kN
Hollow chalky sandstone bricks (KSL) as per DIN EN 106	0.5 kN

In reference to the admissible loads, the individual national safety factors are to be met (e.g. Germany: 3). Comply with approval indications.



TASSELLO H3



RANGE AVAILABLE

<i>Insulation thickness (mm)</i>		<i>Name</i>	<i>Packaging units</i>
On new substrates ¹	On old substrates ²		
40	-	075	200
60	40	095	200
80	60	115	200
100	80	135	200
120	100	155	200
140	120	175	100
160	140	195	100
180	160	215	100
200	180	235	100

¹ Glue thickness 10 mm

² Glue thickness 10 mm plus thickness of old plaster 20 mm



N.B. This Technical Information Sheet is compiled to the best of our technical/scientific knowledge. Nevertheless, it is not binding and does not imply that we are responsible, as the conditions of use are outside our control. It is recommended that the product is always checked as being suitable for the specific application.

IVAS Industria Vernici S.p.A. – Via Bellaria, 40 – 47030 San Mauro Pascoli (FC) – Italy
Phone +39 0541 815811 – Fax +39 0541 815815
www.gruppoivas.com – ivas@gruppoivas.com / www.termok8.com – info@termok8.com

Company with quality management system certified UNI EN ISO 9001