


VITA WASH

Technical Sheet - Ed. 06/2021



Hypoallergenic, washable water-based paint

DESCRIPTION

Hypoallergenic, washable water-based paint dermatologically tested with test report No. 263/14/04 (ISPE) certifying that it is harmless to humans and thus suitable to rooms accommodating allergy sufferers. The disruptive action of aldehydes is certified by Istituto Giordano certificate No. 326956. For professional use. For indoor use.

MAIN PROPERTIES

- Improves living comfort
- Low odour
- Hypoallergenic



TECHNICAL DATA

Classification UNI 8681	One-pack, physical drying, matt, acrylic topcoat paint dispersed in water. (B4.C.O.A.2.FA)
Film appearance EN 13300	Matt (≤ 10 gloss 85°)
Thickness EN 13300	Class A, fine ($< 100 \mu\text{m}$)
Hiding power EN 13300	Class 2
Wet abrasion resistance EN 13300	Class 3
Specific weight	$1620 \pm 50 \text{ g/l}$
pH	7-8
Type of binder	Acrylic
Solid content	$65 \pm 2\%$
Liquid water permeability EN 1062	Class V1 - High
Drying time	Can be overpainted after 4 hrs, completely dry after 12 hrs
VOC	Cat A/a: limit 30 g/l (2010) This product contains a maximum of 30 g/l of VOCs

VITA WASH

Technical Sheet - Ed. 06/2021



CHARACTERISTICS

Colour range	White and Colours can be produced with the You Color tinting system
Coverage	With the application of 2 coats: 4-5 m ² /l
Coverage per pack	(12 l): 60 m ² , approx. Coverage varies according to substrate absorption.
Dilution	30-40% = 300-400 ml per litre of product
Diluted with	Water
Overpaintable	Compatibility with other products: compatible with all water-based products

APPLICATION

Suitable Substrates:

Cement-based plaster, painted plaster, lime-based plaster and paint, exposed reinforced concrete, precast concrete features and panels, gypsum and fibre cement walls and features.

Preparation of the Substrate:

All substrates must be free of release agents and must be dry, clean and coherent. Plasters must be sufficiently cured according to the type of material and manufacturer's instructions. On surfaces with mould or algae, first apply a coat of Sana Solux and wait at least 24 hours before proceeding as indicated in the technical data sheet. In the case of old paint or dusty substrates, we recommend applying a coat of ACRILICA 100 consolidating primer or removing them if this is not sufficient.

Application Procedure:

Dilute VITA WASH as indicated and mix with a low speed mixer. Apply two coats, waiting at least 4 hours between coats. For brush or roller painting, to achieve a uniform appearance, cross the direction of strokes during application.

Type of Equipment:

brush, roller, airless spraying equipment

Ambient Conditions:

min +5°C max +35°C max RH 80%

STORAGE

Packaging:

12 l – 5 l

Duration and Preservation:

1 year when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight

Dispose of in accordance with local regulations.

For information on possible hazards, refer to the safety data sheet

TECHNOLOGIES/CERTIFICATIONS

